

Techniques for Distributed Reachability Analysis with Partial Order and Symmetry based Reductions

Janardan Misra

HTS (Honeywell Technology Solutions) Research Lab
151/1 Doraisanipalya, Bannerghatta Road,
Bangalore 560 076, India
Email: janardan.misra@honeywell.com

Suman Roy *

SETLABS, Infosys Technologies Ltd.
#44 Electronic city, Hosur Road,
Bangalore 560 100, India.
Email: suman_roy@infosys.com

January 1, 2009

Abstract

In this work we propose techniques for efficient reachability analysis of the state space (e.g., detection of bad states) using a combination of partial order and symmetry based reductions in a distributed setting. The proposed techniques are focused towards explicit state space enumeration based model-checkers like SPIN. We consider variants for both depth-first as well as breadth-first based generation of the reduced state graphs on-the-fly.

Contents

1	Introduction	2
2	Background	2
2.1	Centralized DFS Algorithm	3
2.2	Centralized BFS Algorithm	4
2.3	Basic Distributed DFS Algorithm	4
2.4	Partial Order Reduction	6
2.5	Distributed DFS Algorithm with Partial Order Reduction	8
2.6	Symmetry in Model Checking	10
3	Extended Distributed DFS Algorithms	11
3.1	A Distributed DFS Algorithm with Symmetry Reduction	11
3.2	A Distributed DFS Algorithm with both Partial Order and Symmetry Reductions	12

*Work done when authod was associated with HTS.

4	Extended Distributed BFS Algorithms	13
4.1	A BFS Algorithm with Partial Order Reduction	13
4.2	A Distributed BFS Algorithm with both Partial Order and Symmetry Reductions	14

1 Introduction

State space explosion is a fundamental bottleneck in verifying large scale industrial systems (software and hardware) using model checking methods [6, 2]. Primarily the problem is the result of thrashing owing to excessive page faults as the state space becomes too large to be contained in the main memory. There are several approaches to (partially) overcome the problem. Partial order and Symmetry based methods for state space reduction are the most important among them. Distributed verification framework is yet another important measure to overcome the memory limitations.

Partial order based methods exploit the independence of actions to reduce the size of the state space. The basic idea is that given a set of interleaving sequences of actions one can define sequences that are equivalent upto reordering of independent actions. For all those specifications, which do not distinguish between the equivalent sequences, one can consider a representative subset of sequences from each equivalent class. This generates a reduced state space including only a subset of sequences. Most methods work by exploring a subset of the actions enabled from a state. The subset is selected according to some constraints that guarantee that enough representatives, at least one from each equivalent class, will be generated.

On the other hand symmetry based methods exploit the architectural symmetry present in the system description. Finite state concurrent systems frequently contain replicated components. For example, a network protocol might involve a large number of identical processes communicating in some fashion. Hardware devices also contain memories with replicated components. Thus knowledge of the presence of identical components can be used to generate reduced models of these systems because presence of symmetry in the system induces a transition structure preserving equivalence relation on the state space. Thus while performing model checking one can discard a state if another equivalent state has already been considered.

Distributed methods basically aim toward distributing the memory requirement for storing the state space on many processing nodes on a network/cluster without incurring high communication overhead. Often this distribution of model checking process actually helps in overcoming the memory limitations for large state spaces rather than scaling the processing time.

In this invention, we propose a design framework for efficient model checking of the reachability properties (e.g., detection of bad states) using a combination of partial order and symmetry based reductions in a distributed setting. We consider variants for both depth first traversal and breadth first traversal.

2 Background

Preliminaries

A *Labeled Transition System* (LTS) is a tuple (S, R, Act, s_0, L) , where S is a finite set of states and $s_0 \in S$ is an initial state. Act is a (possibly infinite) set of action-labels.

$R \subseteq S \times Act \times S$ is a transition relation such that $(s, \alpha, s') \in R, \alpha \in Act$ is also written as $s \xrightarrow{\alpha} s'$. $L : S \rightarrow 2^{AP}$ is the state labeling function such that $\forall s \in S, L(s)$ defines the subset of propositions true in s . For example, if v is a boolean variable live in state s , then $v \in L(s)$ indicates that when system reaches state s , $v = True$ and $v \notin L(s)$ denotes that $v = False$. AP is the set of all atomic propositions. Let $(\forall s \in S) enabled(s) = \{\alpha \in Act \mid \exists s' \in S \text{ s.t. } s \xrightarrow{\alpha} s'\}$, be the set of all the transitions enabled in a state s . In case of deterministic processes, we write, $s' = \alpha(s)$ for $s \xrightarrow{\alpha} s'$ and for non deterministic processes, we write, $s' \in \alpha(s)$ for $s \xrightarrow{\alpha} s'$. In the following discussion, we will only consider deterministic processes, though the discussions can be smoothly extended to the case of non deterministic processes.

In practice, a typical system model may contain several concurrent processes such that a *global state* refers to the valuations for all variables and *local state* of a process is restricted to the valuations only for those variables accessible to the process.

2.1 Centralized DFS Algorithm

We now recall the basic Depth First Search (DFS) algorithm used to explicitly construct the state graph of a given transition system:

```
// Centralized DFS Based State Space Generation

gen_state_graph() {
  V := {} /* set of generated states */
  Stack U := {} /* stack of states */
  dfs(Start_state)
}

dfs(s) {
  if (s is not in V)
    V := V + {s}
  push_stack(U, s)
  for each (sequential process P)
    nxt := all transitions of P enabled in s
    for each (t in nxt)
      st := t(s)
      dfs(st)
  pop_stack(U)
}
```

We assume a system model containing several concurrent processes. The stack (U) contains the states generated while traversing from the initial state to the current state. The set of visited states V is implemented by a hash table with collision lists, which is generally the most memory consuming data structure, its size being proportional to the number of states in the state graph. Also the stack data structure can consume a considerable amount of memory, because its size is proportional to the depth of the state graph, which, in some cases, can be comparable with the number of states.

2.2 Centralized BFS Algorithm

Basic implementation of Breadth First Search (BFS) based state space generation is not much different from DFS. Instead of a search stack, it uses a queue, which allows insertion and deletion operations in first-in-first-out basis. Successor states are inserted to the tail of the queue (`add_q(Q, s)`) and states for expansion are removed from the front of the queue (`pop_q(Q)`).

```
// Centralized BFS Based State Space Generation
```

```
gen_state_graph() {
    V := {}
    Queue Q = {} /* Queue of states to be expanded. */
    start(Start_state);
}

start(s) {
    add_q(Q, s)
    V = V + {s}
    bfs(Q)
}

bfs(Q) {
    s = pop_q(Q)
    for each (sequential process P)
        nxt := all transitions of P enabled in s
        for each (t in nxt)
            succ = t(s) /* t(s) is the state reached on
                           taking transition t from state s */
            if (succ is not in V)
                add_q(Q, succ) /* Insert succ at the tail of Q */
                V = V + {succ} /* Add succ to State graph V */
        if (Q != {})
            bfs(Q)
}
```

Unlike DFS, BFS cannot be extended smoothly to detect cycles. Again contents of queue Q are not sufficient for traversing an error path and more information such as a link to parent node is required to trace any such error path. Nonetheless, if an error state is encountered, BFS yields shortest path from the start state.

2.3 Basic Distributed DFS Algorithm

For the distributed computation we assume a network of collaborating processors with no global memory under MIMD (multiple input multiple data) architecture. Communication among these processors is realized by means of message passing only. The basic idea behind the parallelization (distribution) is to divide the generation of the state graph into independent subtasks that can be performed in an arbitrary order in parallel. This is achieved by dividing state transition system into partitions, one partition for each processor. In practice, it results into splitting the search stack

into parts determined by fully expanded states such that each processor operates only on its part - the local search stack ($V[i]$). Thus every node in the network owns one of the state subsets, and is responsible for holding the states it owns and for computing their successors. When a node computes a new state, it first checks if the state belongs to its own state subset or to the subset of another node. If the state is local, the node goes ahead as usual, otherwise a message containing the state is sent to the owner of the state. Received messages are held in a queue and processed in sequence. distributed termination algorithms, e.g., ring algorithms [1] can be used when all queues are empty and all nodes are idle to terminate the verification.

The following pseudo-code illustrates the DFS based algorithm used in the distributed version as described in [14]:

```
// Distributed DFS Based State Space Generation

Search(i, Start_state) {
    V[i] := {} /* Set of already visited states on processor i */
    U[i] := {} /* Local stack at processor i */
    j := partition(Start_state)
    if (i == j)
        push_stack(U[i], Start_state)
    visit(i)
}

visit(i) {
    receive();
    /* receive() accepts states generated at other processors to
       be owned by this processor. It adds these states to U[i]. */

    while(True)
        while (U[i] != {})
            s: = top_stack(U[i])
            dfs(i, s)
}

/* Each processor i on the network computes its own local search space. */

dfs(i, s) {
    if (s is not in V) /* For this we need to check for all the state-lists
                        across (all) processors in the network.*/
        V[i] := V[i] + {s}
        push_stack(U[i], s)
        for each (sequential process P)
            nxt := enabled transitions of P in s
            for each (t in nxt)
                st := t(s)
                j := partition(st)
                if (i == j)
                    dfs(i, st)
                else
```

```

        send(st, j)
    pop_stack(U[i])
}

```

It is assumed that all the processors on the network are given unique integer identifiers at the beginning. And function `partition(s)` returns the identifier of the processor to own the state `s`. `visit()` continually looks for received messages containing states and their history and adds these states to local queue.

2.4 Partial Order Reduction

As discussed before, the state space explosion is one of the fundamental bottlenecks for applying model checking algorithms on large complex systems. In case of asynchronous systems with large number of concurrently active processes, the state space explosion problem arises out of the interleaving semantics implying all possible interleaved ordering of transitions of these processes. In fact, for a set of just n transitions, which can be executed concurrently, there are $n!$ different ordering and 2^n different states. Now if the specification does not distinguish between these different orderings then only one ordering with just $n + 1$ states is sufficient to consider. This is what is essentially exploited in the method of partial order reduction (POR) [12]. To achieve this, POR methods exploit the commutativity of concurrently executed transitions, which result in the same state when executed in different order. Thus it is primarily suited for asynchronous systems/protocols since in synchronous systems concurrent actions are executed simultaneously rather than being interleaved.

The POR can be achieved by modifying the basic DFS procedure as described in Section 2.1. The search starts with the initial state s_0 and proceeds recursively. For each generated state s it selects only a subset $ample(s) \subseteq enabled(s)$ of enabled transitions, yielding reduced state graph.

```

// Partial Order Reduction with basic DFS

Search() {
    V := {} /* State Graph - set of visited states */
    Stack U := {} /* DFS stack of states */
    dfs(Start_state)
}

dfs_po(s) {
    if (s is not in V)
        V := V + {s}
        push_stack(U, s)
        for each (sequential process P)
            nxt := all transitions of P in ample(s)
            for each (t in nxt)
                st := t(s)
                dfs(st)
        pop_stack(U)
}

```

The main step of the algorithm is to formulate an effective and efficient way to determine $ample(s)$ for any given state s such that the verification result must be

the same for the reduced and original graph. This is achieved by defining function $ample()$ in accordance with the correctness preserving conditions that are commonly known as conditions **C0-C3** ([6].) We will discuss only conditions **C0-C2**, which are sufficient to verify the safety properties. Further details on these conditions can be found in [6].

- **C0:** $(\forall s \in S) ample(s) = \emptyset \Leftrightarrow enabled(s) = \emptyset$

This condition guarantees that if a state has a successor then reduced state graph will also have a successor for this state. As a consequence this constraint ensures that presence of a deadlock in the reduced graph also implies a deadlock in the original state graph.

- **C1:** For each state $s \in S$, along every path in the full state graph that starts at s , if there exists some action $\beta \in Act$, which is dependent on some action appearing in $ample(s)$, then β cannot be executed without a transition in $ample(s)$ occurring first.

Note that this condition is not immediately checkable by examining only the current state since it refers to future states in the full state graph, which might not even be present in the reduced graph. In worst case it might demand constructing the full state graph since checking it turns out to be as hard as solving the Reachability problem for the full state graph. Therefore in practice we avoid checking **C1** for all arbitrary subsets of enabled transitions and instead use heuristics such as the one presented in [6], though we might not always achieve the optimal reduction.

Condition **C2** is based upon the observation that if there exist a cycle in the reduced state graph and there exist some action which was enabled in a state along the cycle in the full state graph but was not considered in any of the ample sets for the states in the cycle, then it will get permanently ignored (*ignoring problem*) in the reduced state graph. To avoid such ignoring of transitions we consider the following condition:

- **C2 (Cycle proviso):** For every cycle in the reduced state graph, say $C = s_0 \xrightarrow{\alpha_0} s_1 \xrightarrow{\alpha_1} s_2 \dots s_n \xrightarrow{\alpha_n} s_0$, we have $\bigcup_{s_i \in C} ample(s_i) = \bigcup_{s_i \in C} enabled(s_i)$.

In practice cycle proviso is efficiently implemented with respect to the specific traversal algorithm used for generating the state space. In the usual DFS based scenario following stronger proviso is instead checked:

- **C2* (Cycle proviso for DFS):** $(\forall s \in S) ample(s) \subset enabled(s) \Rightarrow \nexists \alpha \in ample(s) \text{ s.t. } \alpha(s) \in U$, where U is the list of states in the DFS stack.

The above three conditions are sufficient to verify any *equivalence robust* property (see [13] for details), which include both safety as well as fairness properties. Determining optimal ample sets for all the states in an arbitrary state graph is a hard problem (with respect to space requirements) particularly when we aim to calculate these ample sets per state, on-the-fly, while generating the graph. Therefore, in practice, heuristics are used instead to check the conditions. Below we present one such heuristic discussed in [6] for **C2/C2***.

```

// Heuristic for ample()

ample(s) {
  for each (sequential process Pi such that Ti(s) != {})
    if( check_C1(s, Pi) AND check_C2*(s, Ti(s))
        AND check_C3(s, Ti(s)))
      return Ti(s)
  return enabled(s)
}

check_C2*(s, X) {
  for all (t in X)
    if (t(s) in V)
      return False
  return True
}

```

However, if we consider a concurrent system as a parallel composition of sequential processes, an obvious candidate for $ample(s)$ is the set $Ti(s)$ of transitions enabled in s for some process Pi . Because the transitions in $Ti(s)$ are interdependent, an ample set for s must include either all of the transitions or none of them. To construct an ample set for the current state s , we start with some process Pi such that $Ti(s) \neq \emptyset$. We want to check whether $ample(s) = Ti(s)$ satisfies all conditions **C1**, **C2/C2***, and **C3**. If either of these remain unsatisfied for all the processes active in state s , we take $ample(s) = enabled(s)$.

2.5 Distributed DFS Algorithm with Partial Order Reduction

A distributed version of the DFS based algorithm for PO reduction was presented in [5, 18]. We will discuss their approach in this section, which will be augmented with symmetry based reductions later. The key part of such an algorithm is the distributed checking of the ample conditions.

While conditions **C0** and **C1** can be checked locally, checking condition **C2/C2*** requires special consideration in a distributed environments. Therefore aim is to define a counter part of the condition **C2*** for the DFS based generation of the state transition system which is distributed among several processors. Motivated by the observation that during the DFS search only a part of the search stack is needed in order to ensure the condition **C2***, authors propose a variant of **C2***. In particular, since the relevant part of the search stack lies between the top of the stack and the topmost state that has been fully expanded. This is because after a state has been fully expanded (i.e., $ample(s) = enabled(s)$) all the cycles reaching this state through the search stack contain this state as a fully expanded one. Based on this simple observation authors suggest to split the reduction (generation) process into independent subtasks such that each time a state is fully expanded, a new search with an empty search stack is started. This is particularly suitable for distribution since it does not need to care about transferring search stacks among the processors. Several subtasks can be performed in parallel on different processors. To deal with “global cycles” (stretching over more than one processor), fully expand a state whenever crossing to a different processor.

Thus, each node maintains a stack states from which the generation of the reduced state transition system is to be started. A *manager* initiates the entire computation by starting the first DFS procedure from the initial state. Whenever a new state s is visited a set $ample(s) \subseteq enabled(s)$ of transitions is computed. Always a set that fulfills the ample conditions is selected; in particular it does not include a transition leading to a search stack nor to another node. If such a set can not be found, the current state is fully expanded.

There are two possible scenarios. In case the state s is fully expanded, every successor s' of the state s is inserted into the stack. If $owner(s')$ differs from $owner(s)$ a message is sent to the owner of s' to do so. The DFS then backtracks from the state s . Otherwise, the DFS continues generating the state transition system following transitions from $ample(s)$ only. After the DFS ends, all incoming messages are processed. Then a state from the stack is picked and a new DFS is initiated from it. This step is repeated until the stack is empty. Once the stack is empty and there are no incoming messages, the node starts to *idle*. If all nodes are idle and there are no pending messages the algorithm terminates.

The modified algorithm for computing ample set in distributed setting is presented as following: Note that only change is required in $check_C2^*(\cdot)$.

// Modified Heuristic for C2*

```
ample(s) {
  for each (sequential process Pi such that Ti(s) != {})
    if ( check_C1(s, Pi) AND check_C2*(s, Ti(s))
        AND check_C3(s, Ti(s)))
      return Ti(s)
  return enabled(s)
}

.
.
.

check_C2*(s, X){
  for all (t in X)
    if ( (t(s) is in U[i]) OR
        (partition(t(s)) < i) )
      return False
  return True
}
```

For improving the efficiency of cycle detection a state is sent to the owner node only if the id of the owner is greater than the id of the current node. Notice that now $check_C2^*(s, X)$ would detect a cycle if there exist some successor of state s , which is already present in the local search stack $U[i]$ OR the id for the owner of successor state is strictly less than the id for the current node i - this is because - *such a state would imply that there must exist some other state on the path from the start state to the current state which would have been visited by some other node earlier, hence closing the cycle.*

Based upon the distributed version of determining $C2^*$, we can describe the complete distributed DFS algorithm with POR as follows:

```

// Distributed DFS algorithm with Partial Order reduction

Search(i, Start_state) { .. }

visit(i) {
  while(True)
    while (U[i] != {})
      s: = extract(U[i])
      ddfs_po(i, s)
}

ddfs_po(i,s) {
  /* we need to check if state s is already generated */
  if (s is not in V)
    V[i] := V[i] + s
    push_stack(U[i], s)
    for each (sequential process P)
      nxt := all enabled transitions of P in ample(s)
      for each (t in nxt)
        st := t(s)
        j := partition(st)
        if (i == j)
          ddfs_po(i, st)
        else
          send(st, j)
    pop_stack(U[i])
}

```

2.6 Symmetry in Model Checking

Yet another way to combat the state space explosion problem is to exploit symmetries in a system description [7, 8, 10, 15]. To illustrate, consider a mutual exclusion protocol based on semaphores. The (im)possibility for processes to enter their critical sections will be similar regardless of their identities, since process identities (pids) play no role in the semaphore mechanism. More formally, the system state remains behaviorally equivalent under permutations of pids. During state-space exploration, when a state is visited that is the same, up to a permutation of pids, as some state that has already been visited, the search can be pruned. The notion of behavioral equivalence used (bisimilarity, trace equivalence, sensitivity to deadlock, fairness, etc.) and the class of permutations allowed (full, rotational, mirror, etc.) may vary, leading to a spectrum of symmetry techniques.

The two main questions in practical applications of symmetry based techniques are how to find symmetries in a system description, and how to detect, during state-space exploration, that two states are equivalent. To start with the first issue: as in any other state-space reduction method based on behavioral equivalences, the problem of deciding equivalence of states requires, in general, the construction of the full state space. Doing this would obviously invalidate the approach, as it is precisely what we are trying to avoid. Therefore, most approaches proceed by listing sufficient conditions that can be statically checked on the system description. The

second problem, of detecting equivalence of states, involves the search for a canonical state by permuting the values of certain, symmetric, data structures. In [7] it was shown that the problem is at least as hard as testing for graph isomorphism, for which currently no polynomial algorithms are known. Furthermore, this operation must be performed for every state encountered during the exploration. Solutions proposed in the literature either deal with incomplete equivalence classes for which the canonicalization problem has polynomial solution [7] or use heuristic strategies [8, 15].

A common heuristic approach is to use a representative function, $rep : S \rightarrow S$ that, given a state s , returns an representative state from the equivalent class containing s , induced by symmetry transformation on the system. For an equivalence class C , the states in $\{rep(s) | s \in C\}$ are called the *representatives* of C . Clearly, if $rep(s) = rep(t)$ then states s and t are equivalent. The reverse does not hold in general, but the smaller the set of all representatives of a class, the more often it will hold. The definition of the representatives is usually based on some partial ordering on states, e.g. by taking as representatives those states that are minimal in a class, relative to the ordering. If the ordering is total, then the representatives are unique for their class.

3 Extended Distributed DFS Algorithms

3.1 A Distributed DFS Algorithm with Symmetry Reduction

Assuming $rep(s)$ is available, we can modify the distributed DFS based state space generation algorithm presented in the Section 2.3 as follows:

```
// Distributed DFS algorithm with Symmetry reduction

Search(i, Start_state) { ... }

visit(i) { ... }

dfs(i,s) {
  if (rep(s) is not in V)
    V[i] := V[i] + {rep(s)} /* Note that we store only rep(s), not s. */
    push_stack(U[i], s)
    .
    .
    .
}
```

Theorem 3.1 (Correctness) *The reduced state graph generated by the above algorithm is equivalent to the full state graph under reachability properties.*

Proof Sketch. Follows from the correctness of basic distributed DFS algorithm and function $rep()$. This is based upon the observation that steps in the basic distributed DFS algorithm do not distinguish between state s and $rep(s)$. Therefore algorithm would generate symmetry reduced graph consisting of states returned by $rep()$. ■

3.2 A Distributed DFS Algorithm with both Partial Order and Symmetry Reductions

We can extend the basic DFS algorithm presented in the Section 2.4 to handle both partial order and symmetry based reductions in a distributed setting.

```
// Distributed DFS algorithm with both
// Partial Order and Symmetry Reductions //

Search(i, Start_state) { ... }

visit(i) { ... }

dfs_po_symm(i, s) {
  /* we need to check if rep(s) is already in
  the stack across (all) processors.*/

  if (rep(s) is not in V)
    V[i] := V[i] + rep(s) /* Note that we store only rep(s), not s. */
    push_stack(U[i], rep(s))
    for each (sequential process P)
      nxt := all transitions of P in ample(s)
      for (each t in nxt)
        st := t(s)
        j := partition(st)
        if (i == j)
          dfs_po_symm(i, st)
        else
          send(j, st) /* Send the state st to its owner j */
      pop_stack(U[i])
}

check_C2*(s, X){
  for all (t in X)
    if ( (rep(t(s)) is in U[i]) OR
        (partition(rep(t(s))) < i) )
      return False
  return True
}
```

Note that $check_C2^*(s, X)$ returns True only if $rep(t(s))$ is already present in local search stack OR the id of the owner of the representative of the successor state is less than the id of the current node.

Theorem 3.2 (Correctness) *The reduced state graph generated by the above algorithm is equivalent to the full state graph under LTL_X properties including reachability properties.*

Proof Sketch. It was proved in [9] that LTS generated using $(ample \circ rep)()$ is equivalent to full LTS under LTL_X properties including safety properties. Together with the correctness claim in Theorem 3.1, correctness of the algorithms follows. ■

4 Extended Distributed BFS Algorithms

4.1 A BFS Algorithm with Partial Order Reduction

We can modify the basic BFS algorithm for POR by limiting the transitions per state to the ample sets. These ample sets can be calculated using the heuristics presented in Section 2.4.

```
//Distributed BFS with Partial Order Reduction

Search(i, Start_state) {
  State Space V[i] := {} /* List of visited states for processor i */
  Queue Q[i] := {}      /* local queue at processor i */
  j := partition(Start_state)

  if (i == j)
    add_Q(Q[i], Start_state)
    visit(i)
}

visit(s) { ... }

check_C2*(s, X){
  for all (t in X)
    if ( [t(s) is in V[i]] AND (t(s) is not in Q[i])] OR
        [partition(t(s)) < i] )
      return False
  return True
}

bfs_po(Q, i) {
  s = pop_q(Q[i]);

  for each (sequential process P)
    nxt := all transitions of P in ample(s)
    for each (t in nxt)
      succ = t(s)
      if (succ is not in V)
        j := partition(st)
        if (i == j)
          add_q(Q[i], succ) /* Insert succ at the tail of Q[i] */
          V = V[i] + {succ} /* Add succ to local State graph V[i] */
        else
          send(j, succ) /* Send the state st to its owner j */
      if (Q[i] != {})
        bfs_po(Q[i])
}
```

Notice that a cycle containing state s would be detected if there exist some successor of s in the already generated local state graph $V[i]$ but such a successor is yet to be

expanded OR the owner of representative of the successor i.e. $partition(t(s))$ is less than the id of the current node i .

4.2 A Distributed BFS Algorithm with both Partial Order and Symmetry Reductions

We can extend the algorithm presented in the previous section to handle both partial order and symmetry based reductions in a distributed setting as follows:

```
// Distributed BFS with Symmetry and POR

Search(i, Start_state) { ... }

visit(i) { ... }

check_C2*(s, X){
  for all (t in X)
    if ( [(rep(t(s)) is in V[i]) AND (t(s) is not in Q[i])] OR
          [partition(rep(t(s))) < i] )
      return False
  return True
}

bfs_po_symm(Q, i) {
  s = pop_q(Q[i])

  for each (sequential process P)
    nxt := all transitions of P in ample(s)
    for each (t in nxt)
      succ = t(s)
      j = partition(succ)
      if(rep(succ) is not in V)
        if(j == i)
          add_q(Q[i], succ) /* Insert succ at the tail of Q */
          V[i] = V[i] + {rep(succ)}
          /* Add rep(succ) to local State graph partition V[i] */
        else
          send(j, succ)
      if(Q[i] != {})
        bfs_po_symm(Q, i);
}
```

Notice that a cycle would be detected if there exist some (representative) successor of s in the already generated local state graph $V[i]$ but such a successor is yet to be expanded OR the owner of representative of the successor i.e. $partition(rep(t(s)))$ is less than the id of the current node i .

References

- [1] Rajeev Alur, Robert K. Brayton, Thomas A. Henzinger, Shaz Qadeer, Sriram K. Rajamani: Partial-Order Reduction in Symbolic State Space Exploration. In Computer Added Verification (CAV'97), pp. 340-351, 1997.
- [2] Béatrice Bérard, Michel Bidoit, Alain Finkel, François Laroussinie, Antoine Petit, Laure Petrucci and Philippe Schnoebelen. Systems and Software Verification: Model-Checking Techniques and Tools. Springer, 2001.
- [3] Dragan Bosānački and Gerad J. Holzmann. Improving Spin's Partial-Order Reduction for Breadth-First Search, Model Checking Software: 12th International SPIN Workshop, SPIN 2005, LNCS **3639**, pp. 91–105, Springer, 2005.
- [4] Dragan Bosānački, Stefan Leue and Alberto Lluch Lafuente. Partial-Order Reductions for General State Exploring Algorithms, Model Checking Software: 12th International SPIN Workshop, SPIN 2006, LNCS **3639**, pp. 91–105, Springer, 2006.
- [5] L. Brim, I. Černa, P. Moravec and J. Šimša. Distributed Partial Order Reduction of State Spaces, Electronic Notes on Theoretical Computer Science, Elsevier Science Publishers, 128, 3, p. 63-74, 2005.
- [6] E. M. Clarke, O. Grumberg and D.A. Peled. Model Checking, The MIT Press, 2000.
- [7] E. M. Clarke, R. Enders, T. Filkorn, and S. Jha. Exploiting symmetry in temporal logic model checking. Formal Methods in System Design, **9(1-2)**: pp. 77–104, 1996.
- [8] Dennis Dams, Dragan Bosānački and Leszek Holenderski. Symmetric Spin. International Journal on Software Tools for Technology Transfer, **4(1)**: pp. 92-106, Springer, 2002, also in .
- [9] E.A. Emerson, S. Jha and D. Peled. Combining partial order and symmetry reductions. In E. Brinksma, editor, Tools and Algorithms for the Construction and Analysis of Systems (TACAS '97), pp. 19–34, LNCS 1217, Springer-Verlag, 1997.
- [10] E. Emerson and A. P. Sistla: Symmetry and Model Checking. Formal Methods in System Design, Vol. **9**, Issue 1-2, Special issue on symmetry in automatic verification, pp 105–131, 1996.
- [11] M. Hennessy and R. Milner: Algebraic Laws for Nondeterminism and Concurrency. Journal of the ACM, Vol. **32**, 137–161, 1985.
- [12] G.J. Holzmann and D. Peled. An Improvement in Formal Verification, *Proc. FORTE 1994 Conference*, 1994.
- [13] Robert P. Kurshan, Vladimir Levin, Marius Minea, Doron Peled, Hsn Yenigün: Combining Software and Hardware Verification Techniques. Formal Methods in System Design 21(3): pp. 251-280, 2002.

- [14] F. Lerda and R. Sisto. Distributed-memory model checking in SPIN. In *Proceedings of the 6th International SPIN Workshop on Model Checking of Software (SPIN'99)*, LNCS, volume **1680** pp. 22–39, Springer, 1999.
- [15] Radu Iosif. Symmetry Reduction Criteria for Software Model Checking. In *Proceedings of the 9th International SPIN Workshop on Model Checking of Software (SPIN'02)*, LNCS, pp. 22–41, France, 2002.
- [16] Ratan Nalumasu and Ganesh Gopalakrishnan. An Efficient Partial Order Reduction Algorithm with an Alternative Proviso Implementation. *Formal Methods in System Design*, **20(3)**, pp. 231–247, 2002.
- [17] Combining Partial Order Reduction with On-the-fly model-checking. In *Proceedings of the 1994 workshop on Computer Aided Verification*, pp. 377–390, LNCS 818, Springer 1994.
- [18] Robert Palmer and Ganesh Gopalakrishnan. A Distributed Partial Order Reduction Algorithm. *FORTE*, 370, 2002.
- [19] U. Stern and D. L. Dill. Parallelizing the murphi verifier. In *Proceedings of the 9th International Conference on Computer Aided Verification, CAV*, 1997.